SOLID MEDIUM

12 mm

ALSAFLOOR

All the features of the Solid range, specially designed for smaller areas.



Technical features :

Thickness	12 mm
Clic system	5G ®
V-grooves	On the 4 sides
Panel	HDF
Texture	* In-registered ** Heliochrome In-registered
Class of use	23/33
Abrasion resistance	AC6
Logistics	Dim. = 1286 x 122 mm / 50.62" x 4.80" 1 box = 6 planks = 0,94m² / 10.12 sqf 1 pallet = 78 kits m²/pallet = 73,40 m² / 790.07 sqf Box gross weight = 10,50 kg / 23.15 lb
Pallet weight	819 kg / 1805.59 lb
Warranty	35 years
Number of designs	9

Water resistant **



* Information as to emissions of volatile compounds in the indoor air, which might be harmful to the health when inhaled, on a scale from Class A+ (very low emissions) to C (high emissions).

** No change in appearance and swelling ≤ 0.2 mm. We guarantee water resistance in accordance with NALFA and ISO 4760 standards, subject to compliance with the Alsafloor installation protocol.

ALSAFLOOR

ZI, 1 rue de l'Europe,
67521 Marlenheim France
Tél: +33 (0)3 88 59 29 89
Fax : +33 (0)3 88 59 28 49

A brand of ALSA FLOORING

SOLID MEDIUM

ALSAFLOOR

12 mm



435 JEFFERSON *

Ref : 545933
Gen : 3512485459336



559 CARMINE OAK *

Ref : 589922
Gen : 3512485899224



619 SARDINIA OAK **

Ref : 522594
Gen : 3512485225948



621 CANARIES OAK **

Ref : 522595
Gen : 3512485225955



622 BALEARES OAK **

Ref : 522597
Gen : 3512485225979



701 PLATO *

Ref : 572869
Gen : 3512485728692



702 ARISTOTLE *

Ref : 572871
Gen : 3512485728715



707 GORGIAS *

Ref : 589921
Gen : 3512485899217



708 ULYSSES *

Ref : 589920
Gen : 3512485899200

* In-registered
** Heliochrome In-registered

ALSAFLOOR

ZI, 1 rue de l'Europe,
67521 Marlenheim France
Tél: +33 (0)3 88 59 29 89
Fax : +33 (0)3 88 59 28 49

A brand of ALSA FLOORING