TECHNICAL SHEET
SOLID MEDIUM - 12m

Water resistant**




PRODUCT FEATURES	Warranty		35 years
	Clic system		5G ®
	Bevels		4 bevels
	Wet room compatibility		Water resistant (1)
	Underfloor heating compatibility		Yes, on low-temperature storage underfloor heating and electric underfloor heating. (2)
TESTS AND TECHNICAL FEATURES	PEFC™ and Greenguard + Greenguard Gold		Yes
	Class of use	ISO 10874	23/33
	Abrasion resistance	EN 13329	AC6
	Impact resistance	EN 13329	IC3
	CE and UKCA labelling	EN 14041	Yes (3)
	Health safety labelling		A+ (*)
	DOP number	EN 14041	002-5/RPC/2013
	Slippery	EN 13893	DS
	Reaction to fire	EN 13501-1	Cfl-S1
	Formaldehyde emission	EN 717-1	E1 ≤ 3,5 mg/m².h
	Thermal resistance	EN 12667	0,0967 (m² K)/W
	Thermal conductivity	EN 12667	0,121 W/(m x K)
DIMENSIONS AND LOGISTICS	Thickness		12 mm
	Lenght x Width		1286 x 122 mm / 50.62'' x 4.80''.
	Number of planks / box		6
	Area / box		0,94m² / 10.12 sqf
	Gross weight / box		10,50 kg / 23.15 lb
	Nomber of box / pallet		78
	Area / pallet		73,40 m² / 790.07 sqf
	Gross weight / pallet		819 kg / 1805.59 lb















This information is given for information purpose only and specifications are liable to change without warning.

(*) Information as to emissions of volatile compounds in the indoor air, which might be harmful to the health when inhaled, on a scale from Class A+ (very low emissions) to C (high emissions).
(1) No change in appearance and swelling ≤ 0.2 mm. We guarantee water resistance in accordance with NALFA and ISO 4760 standards, subject to compliance with the Alsafloor installation protocol.
(2) The thermal resistance of Alsafloor laminate flooring allows it to be installed on low temperature storage underfloor heating systems, and electric underfloor heating systems, subject to compliance with the Alsafloor installation protocol.
(3) EC and UKCA marking declaration of conformity available on request on our website. All our products comply with the EN 14041 norm.

ALSAFLOOR
ZI, 1 rue de l'Europe,
67521 Marlenheim France
Tél: +33 (0)3 88 59 29 89
Fax : +33 (0)3 88 59 28 49

Une marque ALSA FLOORING