

ULTRA CLICK 55

2024




Technical features

Thickness	6,5 mm	
Wearlayer	0,55 mm	
Underlay XPO	1 mm	
Clip system	5G	
V-grooves	4	
Panel	SPC	
Surface	Wood aspect ⁺ [In-registered texture] Stone aspect	
Class of use	23/34	
Logistics	Dimensions 1220 x 180 mm	Dimensions 900 x 470 mm
	1 kit = 8 planks = 1,75 sqm	1 kit = 5 tiles = 2,11 sqm
	Kit weight = 18,5 kg	Kit weight = 21,5 kg
	1 palet = 50 kits	1 palet = 32 kits
	sqm/palet = 87,84 sqm	sqm/palet = 67,68 sqm
	1 palet = 945 kg	1 palet = 710 kg
Residential guarantee	30 years	
Number of designs	11	
Fire resistance	Bfl-s1	
Thermal resistance sqm K/W	≤ 0,15	



Fast, precise and precise



* A VOC rating expresses the amount of volatile material in the interior air which may present a health hazard when inhaled. It is measured on a scale from A+ (very low emissions) to C (high emissions).

ALSAFLOORING - ZI, 1 rue de l'Europe,
67520 Marlenheim France
Tél: +33 (0)3 88 59 29 89
Fax : +33 (0)3 88 59 28 49

