

# Allure Herringbone

# 10 mm


Water resistant \*\*

The tradition of Herringbone laying, in 9 new colours and 10 mm thick.



## Technical features :

|                     |                                                                        |
|---------------------|------------------------------------------------------------------------|
| Thickness           | 10 mm                                                                  |
| Clic system         | Xlock                                                                  |
| V-grooves           | On the 4 sides                                                         |
| Panel               | HDF                                                                    |
| Texture             | In-registered                                                          |
| Class of use        | 23/33                                                                  |
| Abrasion resistance | AC6                                                                    |
| Logistics           | Dim. = 644 x 143 mm / 25.35 X 5.63"                                    |
|                     | 1 box = 16 planks = 1,473 m <sup>2</sup> / 15.86 ft <sup>2</sup>       |
|                     | m <sup>2</sup> /pallet = 88,41 m <sup>2</sup> / 951.64 ft <sup>2</sup> |
|                     | 1 pallet = 60 boxes                                                    |
|                     | Box gross weight = 13,50 kg / 29.76 lb                                 |
| Pallet weight       | 810 kg / 1785.74 lb                                                    |
| Warranty            | 35 years                                                               |
| Number of designs   | 9                                                                      |



\* Information as to emissions of volatile compounds in the indoor air, which might be harmful to the health when inhaled, on a scale from Class A+ (very low emissions) to C (high emissions).

\*\* No change in appearance and swelling  $\leq 0.2$  mm. We guarantee water resistance in accordance with NALFA and ISO 4760 standards, subject to compliance with the Alsafloor installation protocol.

ALSAFLOOR

ZI, 1 rue de l'Europe,  
67521 Marlenheim France  
Tél: +33 (0)3 88 59 29 89  
Fax : +33 (0)3 88 59 28 49

A brand of

**ALSA  
FLOORING**

# Allure HERRINGBONE


10 mm



NEW

452 HONEY OAK

Ref : 603335  
Gen : 3512486033351



NEW

464 JASMINE OAK

Ref : 603336  
Gen : 3512486033368



NEW

521 AIDA OAK

Ref : 603334  
Gen : 3512486033344



NEW

901 BERLIN OAK

Ref : 603337  
Gen : 3512486033375



NEW

902 ZINC OAK

Ref : 603338  
Gen : 3512486033382



NEW

903 JARNAC OAK

Ref : 603339  
Gen : 3512486033399



NEW

904 DOHA OAK

Ref : 603340  
Gen : 3512486033405



NEW

906 SEDONA OAK

Ref : 603341  
Gen : 3512486033412



NEW

907 TUNIS OAK

Ref : 603342  
Gen : 3512486033429



ALSAFLOOR

ZI, 1 rue de l'Europe,  
67521 Marlenheim France  
Tél: +33 (0)3 88 59 29 89  
Fax : +33 (0)3 88 59 28 49

A brand of

**ALSA  
FLOORING**