

# Solid plus Herringbone

# 12 mm


Water resistant \*\*

Tradition and authenticity are the hallmarks of this installation;  
the in-registered finish gives the perfect illusion of a real parquet.



## Technical features :

|                     |                                                                        |
|---------------------|------------------------------------------------------------------------|
| Thickness           | 12 mm                                                                  |
| Clic system         | Xlock                                                                  |
| V-grooves           | On the 4 sides                                                         |
| Panel               | HDF                                                                    |
| Texture             | In-registered                                                          |
| Class of use        | 23/33                                                                  |
| Abrasion resistance | AC6                                                                    |
| Logistics           | Dim. = 644 x 143 mm / 25.35 X 5.63"                                    |
|                     | 1 box = 13 planks = 1,197 m <sup>2</sup> / 12.88 ft <sup>2</sup>       |
|                     | m <sup>2</sup> /pallet = 71,83 m <sup>2</sup> / 773.17 ft <sup>2</sup> |
|                     | 1 pallet = 60 boxes                                                    |
|                     | Box gross weight = 13,20 kg / 29.10 lb                                 |
| Pallet weight       | 792 kg / 1746.06 lb                                                    |
| Warranty            | 35 years                                                               |
| Number of designs   | 9                                                                      |



\* Information as to emissions of volatile compounds in the indoor air, which might be harmful to the health when inhaled, on a scale from Class A+ (very low emissions) to C (high emissions).

\*\* No change in appearance and swelling  $\leq 0.2$  mm. We guarantee water resistance in accordance with NALFA and ISO 4760 standards, subject to compliance with the Alsafloor installation protocol.

ALSAFLOOR

ZI, 1 rue de l'Europe,  
67521 Marlenheim France  
Tél: +33 (0)3 88 59 29 89  
Fax : +33 (0)3 88 59 28 49

A brand of

**ALSA  
FLOORING**

# Solid plus Herringbone

**12 mm**



**435  
JEFFERSON**

*Ref : 590258  
Gen : 3512485902580*



**451 BEIGE OAK**

*Ref : 603204  
Gen : 3512486032040*



**465 SANDALWOOD  
OAK**

*Ref : 603206  
Gen : 3512486032064*



**466 DAHLIA OAK**

*Ref : 603205  
Gen : 3512486032057*



**471 SUNSET**

*Ref : 590259  
Gen : 3512485902597*



**529 ALMOND OAK**

*Ref : 590121  
Gen : 3512485901217*



**535 PRALINE OAK**

*Ref : 590261  
Gen : 3512485902610*



**542 CHOKEBERRY  
OAK**

*Ref : 590262  
Gen : 3512485902627*



**903 JARNAC  
OAK**

*Ref : 603207  
Gen : 3512486032071*



**ALSAFLOOR**

ZI, 1 rue de l'Europe,  
67521 Marlenheim France  
Tél: +33 (0)3 88 59 29 89  
Fax : +33 (0)3 88 59 28 49

A brand of

**ALSA  
FLOORING**