

# TECHNICAL SHEET

## Clip400 - 8 mm

Water Resistant \*\*



|                              |                                      |            |                                                                                                                 |
|------------------------------|--------------------------------------|------------|-----------------------------------------------------------------------------------------------------------------|
| PRODUCT FEATURES             | Warranty                             |            | 25 years                                                                                                        |
|                              | Clic system                          |            | 5G®                                                                                                             |
|                              | Bevels                               |            | None                                                                                                            |
|                              | Wet room compatibility               |            | Water resistant (1)                                                                                             |
|                              | Underfloor heating compatibility     |            | Yes, on low-temperature underfloor heating, electric underfloor heating and underfloor heating and cooling. (2) |
| TESTS AND TECHNICAL FEATURES | PEFC (10-31-943) and Greenguard Gold |            | Yes                                                                                                             |
|                              | Class of use                         | ISO 10874  | 23/33                                                                                                           |
|                              | Abrasion resistance                  | EN 13329   | AC5                                                                                                             |
|                              | Impact resistance                    | EN 13329   | IC3                                                                                                             |
|                              | CE and UKCA labelling                | EN 14041   | Yes (3)                                                                                                         |
|                              | Health safety labelling              |            | A+ (*)                                                                                                          |
|                              | DOP number                           | EN 14041   | 002-7/RPC/2013                                                                                                  |
|                              | Slippery                             | EN 13893   | DS                                                                                                              |
|                              | Reaction to fire                     | EN 13501-1 | Cfl-S1                                                                                                          |
|                              | Formaldehyde emission                | EN 717-1   | E1 ≤ 3,5 mg/m².h                                                                                                |
|                              | Thermal resistance                   | EN 12667   | 0,0661 (m² K)/W                                                                                                 |
|                              | Thermal conductivity                 | EN 12667   | 0,122 W/(m x K)                                                                                                 |
| DIMENSIONS AND LOGISTICS     | Thickness                            | mm         | 8                                                                                                               |
|                              | Length x Width                       | mm         | 1286 x 192 mm / 50.62" x 7.56"                                                                                  |
|                              | Number of planks / box               |            | 9                                                                                                               |
|                              | Area / box                           | m²         | 2,222m² / 23.92 sqf                                                                                             |
|                              | Gross weight / box                   | kg         | 16,50 kg / 36.38 lb                                                                                             |
|                              | Number of box / pallet               |            | 48                                                                                                              |
|                              | Area / pallet                        | m²         | 106,67 m² / 1148.19 sqf                                                                                         |
|                              | Gross weight / pallet                | kg         | 792 kg / 1746.06 lb                                                                                             |



This information is given for information purpose only and specifications are liable to change without warning.

(\*) Information as to emissions of volatile compounds in the indoor air, which might be harmful to the health when inhaled, on a scale from Class A+ (very low emissions) to C (high emissions).

(1) No change in appearance and swelling ≤ 0.2 mm. We guarantee water resistance in accordance with NALFA and ISO 4760 standards, subject to compliance with the Alsafloor installation protocol.

(2) The thermal resistance of Alsafloor laminate flooring allows it to be installed on low temperature underfloor heating systems, electric underfloor heating systems and underfloor heating and cooling, subject to compliance with the Alsafloor installation protocol.

(3) EC and UKCA marking declaration of conformity available on request on our website. All our products comply with the EN 14041 norm.

ALSAFLOOR

ZI, 1 rue de l'Europe,  
67521 Marlenheim France  
Tél: +33 (0)3 88 59 29 89  
Fax : +33 (0)3 88 59 28 49

A brand of

**ALSA  
FLOORING**