

TECHNICAL SHEET

Solid Plus - 12 mm

Water Resistant **



PRODUCT FEATURES	Warranty		35 years
	Clic system		5G®
	Bevels		On the 4 sides
	Wet room compatibility		Water resistant (1)
	Underfloor heating compatibility		Yes, on low-temperature underfloor heating, electric underfloor heating and underfloor heating and cooling. (2)
TESTS AND TECHNICAL FEATURES	PEFC (10-31-943) and Greenguard Gold		Yes
	Class of use	ISO 10874	23/33
	Abrasion resistance	EN 13329	AC6
	Impact resistance	EN 13329	IC3
	CE and UKCA labelling	EN 14041	Yes (3)
	Health safety labelling		A+ (*)
	DOP number	EN 14041	002-4/RPC/2013
	Slippery	EN 13893	DS
	Reaction to fire	EN 13501-1	Cfl-S1
	Formaldehyde emission	EN 717-1	E1 ≤ 3,5 mg/m².h
	Thermal resistance	EN 12667	0,0967 (m² K)/W
	Thermal conductivity	EN 12667	0,121 W/(m x K)
DIMENSIONS AND LOGISTICS	Thickness	mm	12
	Length x Width	mm	1286 x 214 mm / 50.62" x 8.43"
	Number of planks / box		6
	Area / box	m²	1,651m² / 17.77 sqf
	Gross weight / box	kg	18,30 kg / 40.34 lb
	Number of box / pallet		48
	Area / pallet	m²	79,26 m² / 853.15 sqf
	Gross weight / pallet	kg	878,40 kg / 1936.54 lb



This information is given for information purpose only and specifications are liable to change without warning.

(*) Information as to emissions of volatile compounds in the indoor air, which might be harmful to the health when inhaled, on a scale from Class A+ (very low emissions) to C (high emissions).

(1) No change in appearance and swelling ≤ 0.2 mm. We guarantee water resistance in accordance with NALFA and ISO 4760 standards, subject to compliance with the Alsafloor installation protocol.

(2) The thermal resistance of Alsafloor laminate flooring allows it to be installed on low temperature underfloor heating systems, electric underfloor heating systems and underfloor heating and cooling, subject to compliance with the Alsafloor installation protocol.

(3) EC and UKCA marking declaration of conformity available on request on our website. All our products comply with the EN 14041 norm.

ALSAFLOOR

ZI, 1 rue de l'Europe,
67521 Marlenheim France
Tél: +33 (0)3 88 59 29 89
Fax : +33 (0)3 88 59 28 49

A brand of

ALSA FLOORING