

TECHNICAL SHEET

PATIO - 8 mm

Water Resistant**



PRODUCT FEATURES	Warranty		25 years
	Clic system		5G
	Bevels		One the 4 sides
	Wet room compatibility		Water resistant (1)
	Underfloor heating compatibility		Yes, on low-temperature underfloor heating, electric underfloor heating and underfloor heating and cooling. (2)
TESTS AND TECHNICAL FEATURES	PEFC (10-31-943) and Greenguard Gold		yes
	Class of use	ISO 10874	23/33
	Abrasion resistance	EN 13329	AC5
	Impact resistance	EN 13329	IC3
	CE and UKCA labelling	EN 14041	Yes (3)
	Health safety labelling		A+ (*)
	DOP number	EN 14041	001-13/RPC/2022
	Slippery	EN 13893	DS
	Reaction to fire	EN 13501-1	Cfl-S1
	Formaldehyde emission	EN 717-1	E1 ≤ 3,5 mg/m ² .h
	Thermal resistance	EN 12667	0,0661 (m ² K)/W
	Thermal conductivity	EN 12667	0,122 W/(m x K)
DIMENSIONS AND LOGISTICS	Thickness	mm	8
	Length x width	mm	1286 x 192 mm / 50.62" x 7.56"
	Number of planks / box		9
	Area / box	m ²	2,222 m ² / 23.92 sqf
	Gross weight / box	kg	16,50 kg / 36.38 lb
	Number of box / pallet		48
	Area / pallet	m ²	106,67 m ² / 1148.19 sqf
	Gross weight / pallet	kg	792 kg / 1746.06 lb



This table is given for information purpose only and specifications are liable to change without warning.

(*) Information as to emissions of volatile compounds in the indoor air, which might be harmful to the health when inhaled, on a scale from Class A+ (very low emissions) to C (high emissions).

(1) No change in appearance and swelling ≤ 0.2 mm. We guarantee water resistance in accordance with NALFA and ISO 4760 standards, subject to compliance with the Alsaflooring installation protocol.

(2) The thermal resistance of Alsaflooring laminate flooring allows it to be installed on low temperature underfloor heating systems, electric underfloor heating systems and underfloor heating and cooling, subject to compliance with the Alsaflooring installation protocol.

(3) EC and UKCA marking declaration of conformity available on request on our website. All our products comply with the EN 14041 norm.