

TECHNICAL SHEET

HORIZON



PRODUCT FEATURES	Warranty		35 years
	Clic system		5G ®
	Bevels		4 painted
	Panel		SPC
	Underlay		Yes, 1,3 mm in XPS
TESTS AND TECHNICAL FEATURES	Impact Sound		21 dB
	Class of use	ISO 16511	23/33
	Underfloor heating compatibility		Yes, on low-temperature underfloor heating systems, electric PRE and PCR below 28 degrees.(2)
	Veranda compatibility		Yes, direct sunlight not recommended
	CE and UKCA labelling	EN 14041	Yes (3)
	Health safety labelling		A+ (*)
	DOP number	EN 14041	221/RPC/2025
	Slippery	EN 13893	DS
	Reaction to fire	EN 13501-1	Bfl-s1
	Formaldehyde emission	EN 717-1	E1
	Thermal resistance	EN 12667	0,060 (m² K)/W
	Thermal conductivity	EN 12667	0,102 W/(m x K)
DIMENSIONS AND LOGISTICS	Total thickness	mm	6,3
	Length x Width	mm	1222 x 190
	Number of planks / box		7
	Area / box	sqm	1,625
	Gross weight / box	kg	17,09
	Number of box / pallet		52
	Area / pallet	sqm	84,5
	Gross weight / pallet	kg	888,72

This information is given for information purpose only and specifications are liable to change without warning.

(*) Information as to emissions of volatile compounds in the indoor air, which might be harmful to the health when inhaled, on a scale from Class A+ (very low emissions) to C (high emissions).

(2) The thermal resistance of Alsaflooring vinyl flooring allows it to be installed on low temperature underfloor heating systems, electric underfloor heating systems and underfloor heating and cooling.

(3) EC and UKCA marking declaration of conformity available on request on our website. All our products comply with the EN 14041 norm.