

PRESTIGE

ENGINEERED WOOD - HDF panel - 1-Stripe
14mm thick - 180 x 1800/2000 mm



PRODUCT FEATURES	Warranty		25 years
	Clic system		Unifit®
	Bevels		On the 4 sides
	Low-temperature hot water		Yes
	Electric radiant floor heating RFH		Yes
	Underfloor heating and cooling system UHCS		Yes (glue-down fitting only)
TESTS AND TECHNICAL FEATURES	PEFC (10-31-943) and Greenguard Gold		Yes
	Class of use	EN 685	33 R2
	CE and UKCA labelling		Yes
	Health safety labelling		A+ (*)
	DOP number		H094P35C01/RPC/2013
	Moisture content		≤ 9 %
	Length tolerance		± 0,1 %
	Width tolerance		± 0,2 mm
	Skew tolerance		≤ 0,1 % on the width
	Flatness tolerance		(l) ≤ 0,3% on the width
	Flatness tolerance (L)		≤ 1% on the length
	Reaction to fire	EN 14342	Dfl-S1
	Formaldehyde emission	EN 717-1	E1 ≤ 3,5 mg/sqm.h
	Thermal resistance	EN 13489	0,096 (sqm K)/W
DIMENSIONS AND LOGISTICS	Thickness	mm	14
	Length x Width	mm	180 x 1800/2000
	Number of planks / box		5
	Area / box	sqm	1.620/1.800
	Gross weight / box	kg	18.31/20.34
	Number of box / pallet		56
	Area / pallet	sqm	89.10/99,00
	Gross weight / pallet	kg	1006.8/1118.7



including 3,5 mm
top layer



* A VOC rating expresses the amount of volatile material in the interior air which may present a health hazard when inhaled. It is measured on a scale from A+ (very low emissions) to C (high emissions)