VAUBAN

ENGINEERED WOOD - HDF panel - 1-Stripe
14mm thick - 90 x 1190 mm

PARQUETERIE BERRICHONNE

PRODUCT FEATURES	Warranty		25 years
	Clic system		Unifit ®
	Bevels		On the 4 sides
	Low-temperature hot water		Yes
	Electric radiant floor heating RFH		Yes
	Underfloor heating and cooling system UHCS		Yes (glue-down fitting only)
TESTS AND TECHNICAL FEATURES	PEFC (10-31-943) and Greenguard Gold		Yes
	Class of use	EN 685	33 R2
	CE and UKCA labelling		Yes
	Health safety labelling		A+ (*)
	DOP number		H094P35C01/RPC/2013
	Moisture content		≤ 9 %
	Length tolerance		± 0,1 %
	Width tolerance		± 0,2 mm
	Skew tolerance		≤ 0.1 % on the width
	Flatness tolerance		(I) ≤ 0.3% on the width
	Flatness tolerance (L)		≤ 1 % on the length
	Reaction to fire	EN 14342	Dfl-S1
	Formaldehyde emission	EN 717-1	E1 ≤ 3,5 mg/sqm.h
	Thermal resistance	EN 13489	0,096 (sqm K)/W
DIMENSIONS AND LOGISTICS	Thickness	mm	14
	Lenght x Width	mm	90 x 1190
	Number of planks / box		8
	Area / box	sqm	0.857
	Gross weight / box	kg	10.12
	Number of box / pallet		56
	Area / pallet	sqm	47.981
	Gross weight / pallet	kg	566.78

14 MM

including 3,5 mm top layer

UNI fit! PATENTED

GO4

33

R2

PEFC 10-31-943 Promouvoir la gestion durable de la forêt www.pefc-france.org

Made in FRANCE

ÉMISSIONS DANS L'AIR INTÉRIEUR* A+ A+ A B C

* A VOC rating expresses the amount of volatile material in the interior air which may present a health hazard when inhaled. It is measured on a scale from A+ (very low emissions) to C (high emissions)

ALSA FLOORING

2, Chemin de la Parqueterie
36120 Ardentes - FRANCE
Tél : +33 (0)2 54 29 19 11
Fax : +33(0)2 54 36 38 18
www.alsaflooring.com