PREMIUM

ENGINEERED WOOD - HDF panel - 1-Stripe
11mm thick - 140 x 1190 mm

Nature Parquet

PRODUCT FEATURES	Warranty		25 years
	Clic system		Unifit ®
	Bevels		On the 4 sides
	Low-temperature hot water		Yes
	Electric radiant floor heating RFH		Yes
	Underfloor heating and cooling system UHCS		Yes (glue-down fitting only)
TESTS AND TECHNICAL FEATURES	PEFC (10-31-943)		Yes
	Class of use	EN 685	33 R1
	CE and UKCA labelling		Yes
	Health safety labelling		A+ (*)
	DOP number		H074P25C01/RPC/2013
	Moisture content		≤ 9 %
	Length tolerance		± 0,1 %
	Width tolerance		± 0,2 mm
	Skew tolerance		≤ 0.1 % on the width
	Flatness tolerance		(l) ≤ 0.3% on the width
	Flatness tolerance (L)		≤ 1 % on the length
	Reaction to fire	EN 14342	Dfl-S1
	Formaldehyde emission	EN 717-1	E1 ≤ 3,5 mg/sqm.h
	Thermal resistance	EN 13489	0,076 (sqm K)/W
DIMENSIONS AND LOGISTICS	Thickness	mm	11
	Lenght x Width	mm	140 x 1190
	Number of planks / box		10
	Area / box	sqm	1,666
	Gross weight / box	kg	15.49
	Number of box / pallet		45
	Area / pallet	sqm	74,97
	Gross weight / pallet	kg	697.23

11 MM

including 2,5 mm top layer

UNI fit! PATENTED

GO4

33

R1

PEFC 10-31-943 Promouvoir la gestion durable de la forêt www.pefc-france.org

Made in FRANCE

ÉMISSIONS DANS L'AIR INTÉRIEUR* A+ A+ A B C

** A VOC rating expresses the amount of volatile material in the interior air which may present a health hazard when inhaled. It is measured on a scale from A+ (very low emissions) to C (high emissions)*

ALSA FLOORING
2, Chemin de la Parqueterie
36120 Ardentes - FRANCE
Tél : +33 (0)2 54 29 19 11
Fax : +33(0)2 54 36 38 18
www.alsaflooring.com